


Basic series  
15 mm embeddable  
increased operating distance  
increased



General specifications	
Switching element function	PNP Make function
Rated operating distance $s_n$	15 mm
Installation	embeddable
Assured operating distance $s_a$	0 ... 12.15 mm
Reduction factor $r_{AI}$	0.3
Reduction factor $r_{Cu}$	0.3
Reduction factor $r_{V2A}$	0.75
Nominal ratings	
Operating voltage $U_B$	10 ... 30 V
Switching frequency $f$	0 ... 200 Hz
Hysteresis $H$	typ. 5 %
Reverse polarity protection	protected against reverse polarity
Short-circuit protection	pulsing
Voltage drop $U_d$	$\leq 3$ V
Operating current $I_L$	0 ... 200 mA
Off-state current $I_r$	0 ... 0.5 mA typ. 0.1 $\mu$ A at 25 °C
No-load supply current $I_0$	$\leq 15$ mA
Indication of the switching state	all direction LED, yellow
Standard conformity	
Standards	IEC / EN 60947-5-2:2004
Ambient conditions	
Ambient temperature	-25 ... 70 °C (248 ... 343 K)
Mechanical specifications	
Connection type	2 m, PVC cable
Core cross-section	0.34 mm <sup>2</sup>
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67

### Connection type:

